

Bayonet Type Thermocouples : T-220/T-221

T - 220 - L - EXA - □ - □
① ② ③ ④

① Lead wire length
② Lead protection : EXA, Element wire (Fiberglass with stainless steel)
③ Lead wire termination
④ Thermocouple type

Example :T-220-2000-EXA-Y-K

T - 221 - L - EXA - □ - □
① ② ③ ④

① Lead wire length
② Lead protection : EXA, Element wire (Fiberglass with stainless steel)
③ Lead wire termination
④ Thermocouple type

Example :T-221-2000-EXA-Y-K

①	Lead wire length	Specify length by "mm" (500mm to 10,000mm)												
②	Lead protection	<table><tr><th>Code</th><th>Details</th></tr><tr><td>EXA</td><td>Element wire (Fiberglass with stainless steel) (1.0/1X2)</td></tr></table>	Code	Details	EXA	Element wire (Fiberglass with stainless steel) (1.0/1X2)								
Code	Details													
EXA	Element wire (Fiberglass with stainless steel) (1.0/1X2)													
③	Lead wire termination	<table><tr><th>Code</th><th>Details</th></tr><tr><td>Y</td><td>Spade lugs for JIS standard "M3" size screw</td></tr><tr><td>R</td><td>Ring lugs for JIS standard "M4" size screw</td></tr><tr><td>M</td><td>Metal connector (SCK-1602-P)</td></tr><tr><td>TE *1</td><td>Thermocouple connector (CSP01+CLP-A+CSP02)</td></tr><tr><td>N</td><td>No terminal lugs *terminal soldered</td></tr></table> * See Page 7. *1 : Other thermocouple connector : See Page 10	Code	Details	Y	Spade lugs for JIS standard "M3" size screw	R	Ring lugs for JIS standard "M4" size screw	M	Metal connector (SCK-1602-P)	TE *1	Thermocouple connector (CSP01+CLP-A+CSP02)	N	No terminal lugs *terminal soldered
Code	Details													
Y	Spade lugs for JIS standard "M3" size screw													
R	Ring lugs for JIS standard "M4" size screw													
M	Metal connector (SCK-1602-P)													
TE *1	Thermocouple connector (CSP01+CLP-A+CSP02)													
N	No terminal lugs *terminal soldered													
④	Thermocouple type	<table><tr><th>Code</th><th>Details</th></tr><tr><td>K</td><td>Type K (Chromel-Alumel)</td></tr><tr><td>J</td><td>Type J (Iron-Constantan)</td></tr><tr><td>T</td><td>Type T (Copper-Constantan)</td></tr></table>	Code	Details	K	Type K (Chromel-Alumel)	J	Type J (Iron-Constantan)	T	Type T (Copper-Constantan)				
Code	Details													
K	Type K (Chromel-Alumel)													
J	Type J (Iron-Constantan)													
T	Type T (Copper-Constantan)													
	Specifications	Class : class 2 * Class 1 is available (Please specify when you order) Element : Single element * Double element is available (Please specify when you order) Measuring junction : Grounded * Grounded type is available (Please specify when you order) Maximum temperature for use <table><tr><th>Thermocouple type</th><th>Operating temperature for regular use</th><th>Maximum temperature</th></tr><tr><td>K</td><td>300°C</td><td>400°C</td></tr><tr><td>J</td><td>300°C</td><td>400°C</td></tr><tr><td>T</td><td>200°C</td><td>250°C</td></tr></table>	Thermocouple type	Operating temperature for regular use	Maximum temperature	K	300°C	400°C	J	300°C	400°C	T	200°C	250°C
Thermocouple type	Operating temperature for regular use	Maximum temperature												
K	300°C	400°C												
J	300°C	400°C												
T	200°C	250°C												
	Reference	Bayonet SUS304 Holder Screw:R(PT)1/8 L=32,40,62 (Specify by ordering) Bayonet SUS303 Holder Screw : M12(P1.75) L=32,62 (Please specify when you order) * Different types of screws are also available.												